Better models are more effectively connected models

Connecteur WG3 Think-Tank Team

João Pedro Nunes¹, John Wainwright², Charles L. Bielders³, Frédéric Darboux⁴, Peter Fiener⁵, David Finger⁶, Laura Turnbull²

1. CE3C – Centre for Ecology, Evolution and Environmental Changes, Faculdade de Ciências, Universidade de Lisboa, 1749-016 Lisboa, Portugal

2. Department of Geography, Durham University, Science Laboratories, South Road, Durham, DH1 3LE, UK

3. Earth and Life Institute – Environmental Sciences, Université Catholique de Louvain, Croix du Sud 2, L7.05.02, 1348 Louvain-la-Neuve, Belgium.

4. INRA, Laboratoire Sols et Environnement, 2 avenue de la Forêt de Haye BP 20163, F-54505 Vandoeuvre-lès-Nancy cedex, France

5. Institut für Geographie, Universität Augsburg, 86135 Augsburg, Germany

6. School of Science and Engineering, Háskólinn í Reykjavík, Menntavegur 1, IS-101 Reykjavík, Iceland

This article has been accepted for publication and undergone full peer review but has not been through the copyediting, typesetting, pagination and proofreading process which may lead to differences between this version and the Version of Record. Please cite this article as doi: 10.1002/esp.4323

This article is protected by copyright. All rights reserved.

ABSTRACT: Water- and sediment-transfer models are commonly used to explain or predict patterns in the landscape at scales different from those at which observations are available. These patterns are often the result of emergent properties that occur because processes of water and sediment transfer are connected in different ways. Recent advances in geomorphology suggest that it is important to consider, at a specific spatio-temporal scale, the structural connectivity of system properties that control processes, and the functional connectivity resulting from the way those processes operate and evolve through time. We argue that a more careful consideration of how structural and functional connectivity are represented in models should lead to more robust models that are appropriate for the scale of application and provide results that can be upscaled. This approach is necessary because, notwithstanding the significant advances in computer power in recent years, many geomorphic models are still unable to represent the landscape in sufficient detail to allow all connectivity to emerge. It is important to go beyond the simple representation of structural connectivity elements and allow the dynamics of processes to be represented, for example by using a connectivity function. This commentary aims to show how a better representation of connectivity in models can be achieved, by considering the sorts of landscape features present, and whether these features can be represented explicitly in the model spatial structure, or must be represented implicitly at the subgrid scale.

KEYWORDS: structural connectivity, functional connectivity, water and sediment transfers, modelling, subgrid processes

Acce

Introduction

The catchment provides a versatile domain for understanding geomorphic and hydrologic processes at a range of spatial and temporal scales. However, interactions, feedbacks and complex behaviour within catchments produce emergent properties which make it difficult to translate understanding between different scales, both in estimating larger-scale properties from smaller-scale observations (upscaling) or smaller-scale patterns from larger-scale outcomes (downscaling). Numerical modelling is often used as a tool to understand catchments and to attempt to overcome these scaling difficulties, either by supplementing observations with model results for unmeasured variables or at unmeasured locations (e.g. Stieglitz et al., 2003; Nunes et al., 2009; Croke et al., 2013), or for designing and testing different conceptual models of catchment behaviour (e.g. Van Nieuwenhuyse et al., 2011; Hoffmann, 2015). To do so, models should be able to reproduce both the patterns and the linkages of water and sediment fluxes within the catchment(s) under simulation - herein referred to as landscape connectivity. Recent theoretical advances have improved the understanding of connectivity and the description of associated processes (Bracken et al., 2013, 2015), and these advances can be used to create better hydrologic and geomorphic catchment models by improving the way in which they represent landscape connectivity. However, achieving these improvements is far from straightforward; so far, there is no clear framework to guide how connectivity should be represented inside model components.

We argue that the path to building better models is to build more effectively connected models, i.e. models which better represent fluxes of water and sediment through space, by better representing connectivity within and between its fundamental spatial units. The aim of this commentary is to suggest some ways in which a better representation of connectivity can be achieved. We discuss improvements in parameterizing connectivity, and propose using the scale of the fundamental modelling unit to select an appropriate combination between parameterized and emergent connectivity modelling approaches.

Representing landscape connectivity

The representation of connectivity in models must first recognize the difference between structural and functional connectivity. The former reflects static properties of the system at a given timescale, while the latter represents the dynamic behaviour of the system at that timescale (Turnbull *et al.*, 2008; Wainwright *et al.*, 2011; With *et al.*, 1997; Wu and David, 2002). The actual separation between structural and functional connectivity depends on the timescale of the analysis, as functional connectivity may act to reorganize the system and change structural connectivity at longer timescales, which must also be considered in model design (Wainwright *et al.*, 2011). Once the timescale for a given model is set, functional connectivity will be represented by the water and material flows simulated by the model, while structural connectivity will be represented by the model's underlying spatial structure. Structural connectivity can be conceptualized as a spatial pattern of interconnected elements, linking the (microscopic) scale of the fundamental units via their basic links to neighbouring units, and the (macroscopic) scale at which the overall behaviour is considered: in this case, the catchment.

The fundamental unit is the lowest level within this spatial hierarchy, i.e. the measurement unit of the entity of interest. In hydrology, the fundamental unit is traditionally defined based on structural characteristics of hydrological networks, such as the channel reach or sub-catchment, but could equally well be defined based on the scale of a process or, for convenience, as a single cell (pixel). Defining the appropriate scale of the fundamental unit should depend on the scale at which it is conceptually robust to work for a given application. However, typically, the fundamental unit is defined based on the scale at which measurements of parameters or processes are made, or at which data are available (often limited by access to DTMs), which does not necessarily equate to the scale(s) at which it is conceptually robust to work (see Grieve *et al.*, 2016). This mismatch between the theoretical and the actual scale of the fundamental unit is a common limitation when designing the spatial structure of models.

Links between fundamental units define the directionality and magnitude of transfers of water or materials among them. In catchment models, these links create a network for the transfers throughout the system from which, ultimately, the larger scale behaviour is determined (see Heckmann and Schwanghart, 2013). The properties of each basic link can be represented as continuous (i.e. based on a process, such as the water flux through a stream reach) or discretized (i.e. classifying the property as high, intermediate, low, null) or even binary (i.e. on/off) (e.g. Larsen *et al.*, 2012). The scale at which fundamental units are represented will affect how links can be represented, and therefore limitations in defining units will affect the structural link network.

Addressing connectivity in models

(i)

Distributed hydrological and sediment-transport models have been developed over the last few decades to take advantage of increased process understanding and availability of spatio-temporal data. To implement the concepts of landscape connectivity in these models (e.g. Bracken and Croke, 2007; Lexartza-Artza and Wainwright, 2009; Western *et al.*, 2001), a range of approaches can be adopted between two extremes (Figure 1):

- A fully explicit approach, in which all system properties and processes considered relevant are explicitly taken into account, and where connectivity is an emergent property from model results – in other words where basic links are considered explicitly; for instance, high-resolution spatially distributed models.
- (ii) An implicit approach, in which some or all connectivity-relevant links and properties are represented through proxies, and processes have been parameterized to include connectivity; for instance, lumped catchment models.
- (iii) Hybrid approaches, standing in-between these extremes, are also possible; for instance, large watershed models linking lumped models of individual catchments to a distributed model of the stream network.



Figure 1: Schematic overview of the different representations of landscape connectivity in different modelling approaches.

A large number of spatially distributed hydrological and erosion models seek to represent the connectivity of most processes explicitly, by attempting to appropriately define the fundamental unit and their links (e.g. De Roo *et al.*, 1996; Cerdan *et al.*, 2002; Nunes *et al.*, 2005; Wainwright *et al.*, 2008), providing a physically based description of the link (e.g. Finger *et al.*, 2011) and, in some cases, including the dynamic evolution of links due to micro- or macro-topographic changes (e.g. Schoorl *et al.*, 2002; Fiener *et al.*, 2008; Ciampalini *et al.*, 2012). However, even in the most complicated of these models, connectivity-relevant properties and processes are only in part represented explicitly, due to (i) the incomplete understanding or coding of processes, (ii) model resolution and computational considerations, and (iii) theoretical limitations to model completeness (Mulligan and Wainwright, 2013a; Rosenblueth and Wiener, 1945). Model resolution is, in fact, often too coarse to represent the system in such a way that connectivity can emerge.

Furthermore, links between fundamental units are often hidden in effective parameters (i.e. model parameters which are different from the equivalent measurement to account for a process which the model structure does not represent), and thus, links do not dynamically interact with connectivity-related processes. A typical case in many runoff models is where random or orientated surface roughness is parameterized (e.g. as static Manning's *n* or roughness height due to tillage operations) without any process interaction (e.g. Smith *et al.* 2007; Williams, 1970; Fiener *et al.*, 2008). These problems may be hidden by the disparity in the scales of the fundamental unit (usually the raster cell) and of the field observation used to evaluate the model (often a catchment outflow), but they are important in the simulation of spatial patterns.

Problems can be circumvented by using the implicit approach: representing finescale structures and processes within coarser-scale modelling approaches, which helps to improve representations of landscape connectivity, and at a lesser cost in terms of data input and computational requirements but at the expense of some loss of accuracy compared to a fully explicit model. This approach is usually adopted by lumped and semi-distributed models used on larger scales, i.e. where the fundamental unit is defined at a much coarser spatial scale (e.g. in SWAT; Arnold and Fohrer, 2005; see discussion in Mulligan and Wainwright 2013b). However, in the implicit approach, connectivity is also often represented by effective parameters with little dynamic evolution or interaction between processes, limiting the simulation of emergent behaviour at the catchment scale. For example, connectivity is implicit in the use of soil moisture to select different rainfall-runoff response functions such as with the Curve Number approach (Garen and Moore, 2005), or in the use of a single value to represent sediment transfer between units, either a fixed percentage (e.g. Watem-Sedem, Van Oost et al., 2000) or a fixed mass (e.g. STREAM, Cerdan et al., 2002), even though these values may, in fact, evolve through space and time.

What is common to many of these approaches is the representation of functional connectivity as a static property or, at best, one with limited changes. Stochastic approaches have been proposed where deterministic links are replaced by all units having a probability of being linked to others (see Hütt *et al.*, 2012, for a non-geomorphologic example), but they still do not overcome the inherently static nature in which the system is represented. Models that attempt to simulate the temporal behaviour of systems cannot represent the evolutionary behaviour of those systems correctly if they do not capture the dynamics of functional connectivity would be to use a connectivity function.

From functional connectivity to connectivity functions

To produce a connectivity function, one must first start with an explicit representation of fundamental units; then, once the emergent behaviour of these links has been described, a simple and sound functional relationship can be derived to represent implicitly the interactions among individual links. A landscape-connectivity function will reflect the connectivity in overland flow or sediment transfer within the unit. Percolation theory provides an example of a conceptual framework in which these relationships can be derived from first principles (e.g. Berkowitz and Ewing, 1998; Darboux *et al.*, 2002; Harel and Mouche, 2014), although more often the relationships are derived by the confrontation of empirical data with transport equations of varying degrees of complexity.

A connectivity function can, in principle, be represented by a binary or continuous approach. A continuous definition does not necessarily lead to a better assessment of connectivity and it is even usual for a connectivity evaluation procedure to start with the binarization of the continuous values of individual links (e.g. Souchère et al., 1998). A simple example of a connectivity-based binary switch at a relatively small scale (DTM grid cell) is when a decision is made regarding flow direction in the presence of orientated roughness whenever the orientation of tillage-induced roughness does not coincide with slope aspect (Souchère et al., 1998; Takken et al., 2001). In this case, the binary switch does not affect whether or not two contiguous cells are connected, but it governs the directionality of the flow, i.e. it controls which neighbouring cell gets connected to the source cell. Other examples of binary connectivity switches in hydrological models include the use of the maximum depression storage as a threshold to transfer flow from one modelling unit to one or more neighbours (Singh and Frevert, 2002), and the so-called "bucket models" in which water is transferred from one soil layer to the next only after the moisture content reaches field capacity (Walker and Zhang, 2001).

Alternatively, a continuous function may be used to describe connectivity whereby units are connected via links with varying levels of connectivity. Taking the examples given above, Razafison *et al.* (2012) introduced a non-binary approach to determine water flow in the topographic or the tillage direction based on an anisotropic friction coefficient; and the LISEM model replaces the maximum depression storage approach by a continuous function governing the rate of water transfer as a function of the degree of filling of the depression storage (De Roo *et al.*, 1996). Other examples of such continuous switches are the recent use of the "porosity concept" to regulate the amount and cross section of flow between adjacent cells (Lane *et al.*, 2004; McMillan and Brasington, 2007).

Antoine *et al.* (1999) developed a more complex approach to express sub-grid water connectivity as a function of the level of depression storage filled, the Relative Surface Connection function (RSCf). Depressions and flow-paths within a given model cell are explicitly simulated from rainfall using a very high resolution (10-mm) DTM. The RSCf can be combined with a weighted surface procedure to generate realistic hydrographs of elementary units (Antoine *et al.*, 2011). Peñuela *et al.* (2015) replaced the need of a high-resolution DTM with a three-point parameterization estimated from slope and structural terrain information for random roughness, which allows the application of this method at the watershed scale.

Building more effectively connected models

Models can effectively integrate connectivity by using connectivity functions. These functions should be selected to represent the fundamental unit for which the model was designed, which can range from small to large scales, e.g. from single DTM grid cells and fields to entire watersheds. Figure 2 provides an initial assessment of the likely scales at which connectivity could be included in model design, and whether the representation of connectivity should be explicit, i.e. allowed to emerge from existing connectivity links; or implicit, i.e. through connectivity functions.

Explicit representation possible (connectivity emerges)



Figure 2: Schematic representation of scales at which certain landscape features that are influential in terms of water or sediment connectivity are resolved explicitly or implicitly in environmental models.

A schematic representation such as this can help decide the appropriate resolution of application for a given model, based on the processes that are represented implicitly. For example, commonly used spatially distributed models such as LISEM (De Roo et al., 1996) or LandSoil (Ciampalini et al., 2012) are typically applied with spatial resolutions between 1 and 10 m. While these relatively fine resolutions should allow them to represent most connectivity processes explicitly, implicit solutions should be found to address, for example, connectivity due to roughness and rills. Moreover, the application of these models with larger-resolutions DTMs such as global datasets with resolutions between 30 and 90 m would stretch their capacities, as it would be difficult for the connectivity effects of vegetation patches, field edges or gullies to be explicitly represented. Past approaches have tried to address this issue using sub-grid scale parameterization (e.g. Zhang *et al.*, 2002), but progress is now needed to integrate sub-grid scale processes in models using connectivity functions to take advantage of the opportunities offered by these datasets.

Model development is always a trade-off between inclusion of detail and parsimony of representation. By considering why parameters may be appropriate at different scales, and how connectivity functions can represent linkages between different scales, we suggest that more robust models can be designed that will require less (or no) empirical calibration, and thus underpin their physical basis and potential for extrapolation. The use of such linkages also supports process based up- or downscaling, and can thus aid in model evaluation and testing where data are only available at very different scales from model implementation. While the increasing availability of high resolution topographic data (e.g. from TLS and UAVs: Ouedraogo et al., 2014; Pineux et al., 2017) means that models could be applied at very high spatial resolutions to account for connectivity explicitly, computational tractability means that it is unlikely that direct advantage can be taken of these data for some time to come. By using these data in the definitions of connectivity functions, direct advantage can be taken of these data immediately, especially if connectivity links across different scales can be defined a priori. More research is required to define connectivity functions that can be applied at a wide range of scales and in relation to different processes, and in particular to define the feedbacks between functional and structural connectivity at different scales.

Acknowledgements

This article supported by COST Action ES1306 Connecteur was (http://connecteur.info/). We would like to thank other colleagues present at the various Action meetings for input and discussion, although the content is the responsibility of the authors. J.P. Nunes was also funded by Fundação para a Ciência e a Tecnologia (research grant IF/00586/2015). We would like to thank three anonymous reviewers whose comments have contributed significantly to the clarification of the ideas presented. The authors have no conflict of interest to declare.

References

- Antoine M, M Javaux, CL Bielders 2009. What indicators can capture runoff-relevant connectivity properties of the micro-topography at the plot scale? *Advances in Water Resources* 32, 1297–1310.
- Antoine M, M Javaux, CL Bielders 2011. Integrating subgrid connectivity properties of the micro-topography in distributed runoff models, at the interrill scale. *Journal of Hydrology* 203, 213–223.
- Arnold JG, N Fohrer 2005. SWAT2000: current capabilities and research opportunities in applied watershed modelling. *Hydrological Processes* 19, 563–572.
- Berkowitz B, RP Ewing 1998. Percolation theory and network modeling applications in soil physics. *Surveys in Geophysics* 19, 23–72.
- Bracken LJ, Croke J 2007. 'The concept of hydrological connectivity and its contribution to understanding runoff-dominated geomorphic systems', *Hydrological Processes* 21, 1749–1763.
- Bracken LJ, J Wainwright, G Ali, D Tetzlaff, MW Smith, S Reaney, A Roy 2013. 'Concepts of hydrological connectivity: research approaches, pathways and future agendas', *Earth-Science Reviews* 119, 17–34.
- Bracken LJ, L Turnbull, J Wainwright, P Bogaart 2015. 'Sediment connectivity: a framework for understanding sediment transfer at multiple scales', *Earth Surface Processes and Landforms* 40, 177–188.
- Cerdan O, Y Le Bissonnais, A Couturier, N Saby 2002. Modelling interrill erosion in small cultivated catchments. *Hydrological Processes* 16, 3215–3226.
- Ciampalini R, S Follain, Y Le Bissonnais 2012. LandSoil: a model for the analysis of erosion impact on agricultural landscape evolution. *Geomorphology* 175, 25–37.

- Croke J, K Fryirs, C Thompson 2013. Channel–floodplain connectivity during an extreme flood event: implications for sediment erosion, deposition, and delivery. *Earth Surface Processes and Landforms* 38, 1444–1456.
- Darboux F, P Davy, C Gascuel-Odoux 2002. Effect of depression storage capacity on overland-flow generation for rough horizontal surfaces: water transfer distance and scaling. *Earth Surface Processes and Landforms* 27, 177–191.
- De Roo APJ, CG Wesseling, CJ Ritsema 1996. LISEM: a single-event physically based hydrological and soil erosion model for drainage basins. I: theory, input and output. *Hydrological Processes* 10, 1107–1117.
- Fiener P, G Govers, K Van Oost 2008. Evaluation of a dynamic multi-class sediment transport model in a catchment under soil-conservation agriculture. *Earth Surface Processes and Landforms* 33, 1639–1660.
- Fiener P, K Auerswald, K Van Oost 2011. Spatio-temporal patterns in land use and management affecting surface runoff response of agricultural catchments—A review. *Earth-Science Reviews* 106, 92–104.
- Finger D, F Pellicciotti, M Konz, S Rimkus, P Burlando 2011. The value of glacier mass balance, satellite snow cover images, and hourly discharge for improving the performance of a physically based distributed hydrological model. *Water Resour. Res.* 47, W07519.
- Garen DC, DS Moore 2005. Curve number hydrology in water quality modeling: uses, abuses, and future directions. *JAWRA Journal of the American Water Resources Association* 41, 377–388.
- Grieve SWD, SM Mudd, MD Hurst 2016. How long is a hillslope? *Earth Surface Processes and Landforms* 41, 1039–1054.
- Harel M-A, E Mouche 2014. Is the connectivity function a good indicator of soil infiltrability distribution and runoff flow dimension? *Earth Surface Processes and Landforms* 39, 1514–1525.

- Heckmann T, W Schwanghart 2013. Geomorphic coupling and sediment connectivity in an alpine catchment — Exploring sediment cascades using graph theory. *Geomorphology* 182, 89–103.
- Hoffmann T 2015. Sediment residence time and connectivity in nonequilibrium and transient geomorphic systems, *Earth-Science Reviews* 150, 609–627.
- Hütt M-T, M Jain, CC Hilgetag, A Lesne 2012. Stochastic resonance in discrete excitable dynamics on graphs. *Chaos, Solitons and Fractals* 45, 611–618.
- Lane, SN, RJ Hardy, L Elliott, DB Ingham 2004 'Numerical modeling of flow processes over gravelly surfaces using structured grids and a numerical porosity treatment', *Water Resources Research* 40, W01302
- Larsen LG, J Choi, MK Nungesser, JW Harvey 2012. Directional connectivity in hydrology and ecology. *Ecological Applications* 22, 2204–2220.
- Lexartza-Artza I, J Wainwright 2009. 'Hydrological connectivity: linking concepts with practical implications', *Catena* 79, 146–152.
- McMillan HK, J Brasington 2007 Reduced complexity strategies for modelling urban floodplain inundation. *Geomorphology* 90, 226–243.
- Mulligan M, J Wainwright 2013a. Modelling and model building, in J Wainwright, M Mulligan (eds) *Environmental Modelling: Finding Simplicity in Complexity*, 7–26, 2nd Edition. Wiley-Blackwell, Chichester.
- Mulligan M, J Wainwright 2013b. Modelling catchment and fluvial processes and their interactions', in J Wainwright, M Mulligan (eds) *Environmental Modelling: Finding Simplicity in Complexity*, 183–206, 2nd Edition. Wiley-Blackwell, Chichester.
- Nunes JP, G Vieira, J Seixas, P Gonçalves, N Carvalhais 2005. Evaluating the MEFIDIS model for runoff and soil erosion prediction during rainfall events. *Catena* 61, 210–228.

- Nunes JP, J Seixas, JJ Keizer, AJD Ferreira 2009. Sensitivity of runoff and soil erosion to climate change in two Mediterranean watersheds. Part II: impact of changes in rainfall, antecedent soil moisture and vegetation cover. *Hydrological Processes* 23, 1212–1220.
- Ouedraogo MM, A Degré, C Debouche, J Lisein 2014. The evaluation of unmanned aerial system-based photogrammetry and terrestrial laser scanning to generate DEMs of agricultural watersheds. *Geomorphology* 214, 339–355.
- Peñuela A, M Javaux, CL Bielders 2015. How do slope and surface roughness affect plot-scale overland flow connectivity? *Journal of Hydrology* 528, 192–205.
- Pineux N, J Lisein, G Swerts, CL Bielders, P Lejeune, G Colinet, A Degré 2017. Can DEM time series produced by UAV be used to quantify diffuse erosion in an agricultural watershed? *Geomorphology* 280, 122–136.
- Razafison U, S Cordier, O Delestre, F Darboux, C Lucas, F James 2012. A shallow water model for the numerical simulation of overland flow on surfaces with ridges and furrows. *European Journal of Mechanics B/Fluids* 31, 44–52.
- Rosenblueth A, N Wiener 1945. The role of models in science, *Philosophy of Science* 12, 316.
- Schoorl JM, A Veldkamp, J Bouma 2002. Modeling Water and Soil Redistribution in a Dynamic Landscape Context. *Soil Science Society of America Journal* 66, 1610-1619.
- Singh VP, D Frevert 2002. *Mathematical Models of Small Watershed Hydrology and Applications*, 950 pp, Water Resources Publications, Littleton CO.
- Smith MW, NJ Cox, LJ Bracken 2007. Applying flow resistance equations to overland flows. *Progress in Physical Geography* 31, 363–387.
- Souchère V, D King, J Daroussin, F Papy, A Capillon 1998. Effects of tillage on runoff directions: consequences on runoff contributing areas within agricultural catchments. *Journal of Hydrology* 206, 256–267.

- Stieglitz M, J Shaman, J McNamara, V Engel, J Shanley, GW Kling 2003. An approach to understanding hydrologic connectivity on the hillslope and the implications for nutrient transport. *Global Biogeochemical Cycles* 17 (4), article number 1105.
- Takken I, G Govers, V Jetten, L Nachtergaele, A Steegen, J Poesen 2001. Effect of tillage and runoff and erosion patterns. *Soil Tillage Research* 61, 55–60.
- Turnbull L, J Wainwright, RE Brazier 2008. A conceptual framework for understanding semi-arid land degradation: ecohydrological interactions across multiple-space and time scales. *Ecohydrology* 1, 23–34.
- Van Nieuwenhuyse BHJ, M Antoine, G Wyseure, G Govers 2011. Pattern-process relationships in surface hydrology: hydrological connectivity expressed in landscape metrics. *Hydrological Processes* 25, 3760–3773.
- Van Oost K, G Govers, P Desmet 2000. Evaluating the effects of changes in landscape structure on soil erosion by water and tillage. *Landscape Ecology* 15, 577–589.
- Wainwright J, AJ Parsons, EN Müller, RE Brazier, DM Powell, B Fenti 2008. 'A transport-distance approach to scaling erosion rates: 3. Evaluating scaling characteristics of MAHLERAN', Earth Surface Processes and Landforms 33, 1113–1128.
- Wainwright J, L Turnbull, TG Ibrahim, I Lexartza-Artza, SF Thornton, RE Brazier
 2011. 'Linking environmental régimes, space and time: interpretations of structural and functional connectivity'. *Geomorphology* 126, 387–404.
- Walker GR, L Zhang 2001. Plot-scale models and their application to recharge studies, in L Zhang, GR Walker (eds) Studies in Catchment Hydrology: The Basics of Recharge and Discharge, Part 10, 29pp, CSIRO Publishing, Melbourne.

- Western, AW, G Blöschl and RB Grayson 2001 'Toward capturing hydrologically significant connectivity in spatial patterns', *Water Resources Research* **37**, 83–97.
- Williams GP 1970. Manning formula a misnomer? *Journal of the Hydraulics Division, American Society of Civil Engineers* 96(HY1), 193–200.
- With KA, RH Gardner, MG Turner 1997. Landscape connectivity and population distributions in heterogeneous environments. *Oikos* 78, 151–169.
- Wu J, JL David 2002. A spatially explicit hierarchical approach to modeling complex ecological systems: theory and applications. *Ecological Modelling* 153, 7–26.
- Zhang X, N Drake, J Wainwright 2002. Scaling land surface parameters for globalscale soil erosion estimation. *Water Resources Research* 38(9), 1180.

Accepted